

MFS8 specifications

| | |
|---------------------------|-----------------------------|
| Number of Cylinders | 2 |
| Output | 8 hp (5.9 kw) |
| Displacement | 209 cc (12.8 cu.in) |
| Bore x Stroke | 55 x 44 mm (2.17 x 1.73 in) |
| Starting | Electric or Manual |
| Control Type | Tiller Handle |
| Gear Shift | Forward - Neutral - Reverse |
| Gear Ratio | 2.08:1 |
| Propeller Selection Range | 6.5" - 9.5" |
| Transom Height | 15", 20" |
| Weight | 81.5 lbs (37 kg) |
| Alternator Output | Optional: 12V, 80W, 6A* |
| Max RPM Range | 5,000 - 6,000 |

Standard features include: Digital CD Ignition System, Start in Gear Protection, Thermostat Controlled Cooling System, Through-The-Prop Exhaust, Oil Pressure Warning, and Shallow Water Drive

*Standard on Electric Start Models



TOHATSU

Feel the Wind™

MFS8



The Tohatsu 8 hp outboard was made to be lightweight and compact without compromising reliability or the quality performance associated with the Tohatsu brand name.

We have maintained the durable standard features while making a fuel-efficient 4-stroke that is easy to transport.



Feel the Wind™